

TECHNICAL DATA SHEET



SUPERPHON[®] HIGH IMPACT WALL PANELS

PRODUCT DESCRIPTION

SuperPhon[®] High Impact Wall Panels have been specifically developed to provide an attractive reverberation control solution for areas of high traffic or where surface impact is expected. SuperPhon[®] is a cost effective panel system with a patented (GB2550373A) high impact resistant layer which provides superior levels of sound absorption due to its unique patented construction that incorporates advanced micro swirl air cells within the panel that significantly enhance the sound absorption particularly at the low end of the frequency spectrum, this extra performance means that when the performance levels are put into the room calculator less panel area is required compared to most other sound absorption panels on the market. These highly robust panels are manufactured to bespoke order and finished with acoustic woven fabric to the front face and edges to deliver an high quality, aesthetic finish.

BENEFITS

- Fully bespoke acoustic solution
- Impact resistant
- 77 colours available over two ranges
- Up to Class 'A' acoustic absorption
- Manufactured to exact project requirements
- Certified by CST Global Centre for Sports Technology
- Approved by ISSS, WSF and ITF
- A solid to wall or 25mm/50mm air gap can be formed on site



SuperPhon® High Impact	
Thickness (mm)	25mm, 40mm and 50mm
Max panel size	3000 x 1200mm

TECHNICAL INFORMATION

The noise absorption coefficient is expressed as a factor. The more sound that a material absorbs, the higher the noise absorption coefficient.

Panel	Air gap	125 Hz	250 Hz	500 Hz	1 KHz	2 KHz	4 KHz	NRC	Class
25mm	0mm	0.08	0.33	0.74	1.08	1.08	1.04	0.80	C
40mm	0mm	0.19	0.73	1.14	1.07	1.02	1.07	1.00	A
50mm	0mm	0.28	0.77	1.15	1.21	1.06	1.12	1.05	A
25mm	25mm	0.16	0.47	0.90	1.18	1.11	1.06	0.90	B
40mm	25mm	0.35	0.87	1.15	1.11	1.10	1.08	1.05	A
50mm	25mm	0.40	0.88	1.16	1.19	1.06	1.06	1.05	A
25mm	50mm	0.23	0.60	1.04	1.19	1.04	1.08	0.95	A
40mm	50mm	0.50	0.88	1.12	1.11	1.04	1.11	1.05	A
50mm	50mm	0.55	0.95	1.16	1.16	1.04	1.11	1.10	A

ACCREDITATION

SuperPhon® High Impact Wall Panels have been tested and certified by the CST Global Centre for Sports Technology, a UKAS approved test house (also approved by the ISSS, World Squash Federation and ITF) and is certified to BS EN 13964, Classes A, B and C for impacts in Sports Halls and Gymnasiums for multi-purpose use, by balls including footballs and hockey balls

APPLICABLE PATENT

Great Britain No. GB2550373A "a sound absorbing impact resistant laminate"

CMS DANSKIN ACOUSTICS

Scotland Office: Tel: **01698 356000** Fax: **01698 372222**
1 Netherton Road, Wishaw, ML2 0EQ

Central/Southern Office: Tel: **01925 577711** Fax: **01925 577733**
Unit 2 Lyncastle Road, Appleton, Warrington, WA4 4SN

Email: info@cmsdanskin.co.uk Website: www.cmsdanskin.co.uk

IMPORTANT: Directions for use are given for guidance only and are not intended to form part of any contract. They should be varied or adapted to suit your particular materials or conditions of use. Goods supplied by the company are made to approved standards from the highest quality raw materials but no warranty or guarantee is given as to their suitability for any particular purpose or application, and no liability is accepted for any loss or damage arising directly or indirectly from the use of the Company's products irrespective of any information given to us as to intended use of such products. It is therefore recommended that prospective users should test a sample of this product under their own conditions to satisfy themselves that the product is suitable for the purpose intended.

CMSDANSKIN
ACOUSTICS

