# **Timber Slat Wall Panel**



## Technical Data Sheet

A constructed wall panel of timber veneered slats stapled to a PET felt backing.

### DIMENSIONS

Length	Width	Depth
3000mm	600mm	13mm
2400mm	600mm	13mm

## **FEATURES and BENEFITS**

## Slats

27mm wide x 13mm deep.

Comprising of a 0.6mm timber veneer bonded to the front of a 12mm black standard MDF with paper backing.

## **PET Felt**

- Decorale Black
- 100% Polyester
- Thermally bonded blend
- 1300g/m<sup>2</sup>

## PACKAGING

Supplied individually in corrugated cardboard that is suitable for recycling.







#### STOCKED VENEERS



## SPECIAL ORDER VENEERS



NOTE: as the veneers are a natural product the colours delivered will not be an exact match to the image printed above



O1698 356000 (Scotland)
O1925 577711 (Central)
enquiries@danskin.co.uk (Scotland)
info@cmsdanskin.co.uk (Central)
www.cmsdanskin.co.uk

CMS Danskin Acoustics is part of the

PERFORMANCE TECHNOLOGY GROUP

www.PerformanceTechnologyGroup.com

IMPORTANT: The information provided within this document is believed correct and to the best of our available knowledge at its revision date and is provided as suggestion for safe handling, storage, transportation, use and disposal. The information should not be considered obligation in respect of warranty of (technical) performance, quality (specification) or suitability for any application or design. The customer must satisfy themself the product (or draft specification) are relevant and suitable for their need and design intent. Prospective users should test a sample of product under their own conditions to satisfy themselves of its suitability for intended purpose and that expert advice be sought where different applications are contemplated. Due to our policy of continuous improvement we reserve the right to alter or amend published specification in any manner is not permitted without our prior written consent.